



elmhurst
energy



SAP Report Submission for Building Regulations Compliance

Client:

Project: Plot 137

Contact: Benjamin Wood
Benjamin Wood
ben.wood@thefesgroup.com

Report Issue Date: 15/03/2021

EXCELLENCE
IN ENERGY
ASSESSMENT

THERMAL BRIDGING

Calculation Type: New Build (As Designed)

Property Reference	007818 - Plot 137		Issued on Date	15/03/2021
Assessment Reference	Rev A	Prop Type Ref	007818-SAP-2328-Semi-MT	
Property	Plot 137			

SAP Rating	84 B	DER	17.48	TER	19.20
Environmental	87 B	% DER<TER	8.95		
CO ₂ Emissions (t/year)	1.08	DFEE	46.10	TFEE	54.05
General Requirements Compliance	Pass	% DFEE<TFEE	14.70		

Assessor Details	Mr. Paul Bainbridge, Paul Bainbridge, Tel: 01904 674890, paul.bainbridge@thefesgroup.com	Assessor ID	p717-0001
------------------	--	-------------	-----------

Client	Larkfleet Group
--------	-----------------

	Junction detail	Source Type	Psi (W/mK)	Length (m)	Result	Reference
External wall	E2 Other lintels (including other steel lintels)	Independently assessed	0.040	10.07	0.40	
External wall	E3 Sill	Independently assessed	0.027	7.26	0.20	
External wall	E4 Jamb	Independently assessed	0.029	15.60	0.45	
External wall	E5 Ground floor (normal)	Independently assessed	0.049	24.60	1.21	
External wall	E6 Intermediate floor within a dwelling	Independently assessed	0.003	24.60	0.07	
External wall	E10 Eaves (insulation at ceiling level)	Independently assessed	0.083	9.25	0.77	
External wall	E12 Gable (insulation at ceiling level)	Independently assessed	0.054	8.05	0.43	
External wall	E16 Corner (normal)	Independently assessed	0.050	9.99	0.50	
External wall	E18 Party wall between dwellings	Table K1 - Default	0.120	9.99	1.20	
Party wall	P1 Party wall - Ground floor	Table K1 - Default	0.160	8.05	1.29	
Party wall	P2 Party wall - Intermediate floor within a dwelling	Table K1 - Default	0.000	8.05	0.00	
Party wall	P4 Party wall - Roof (insulation at ceiling level)	Table K1 - Default	0.240	8.05	1.93	

Total: **8.45** W/mK:
 Y-Value: **0.053** W/m²K:

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

Property Reference	007818 - Plot 137		Issued on Date	15/03/2021	
Assessment Reference	Rev A	Prop Type Ref	007818-SAP-2328-Semi-MT		
Property	Plot 137				
SAP Rating	84 B	DER	17.48	TER	19.20
Environmental	87 B	% DER<TER	8.95		
CO₂ Emissions (t/year)	1.08	DFEE	46.10	TFEE	54.05
General Requirements Compliance	Pass	% DFEE<TFEE	14.70		
Assessor Details	Mr. Paul Bainbridge, Paul Bainbridge, Tel: 01904 674890, paul.bainbridge@thefesgroup.com			Assessor ID	p717-0001
Client	Larkfleet Group				

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

REGULATIONS COMPLIANCE REPORT - Approved Document L1A, 2013 Edition, England

REGULATIONS COMPLIANCE REPORT - Approved Document L1A, 2013 Edition, England

DWELLING AS DESIGNED

End-Terrace House, total floor area 74 m²

This report covers items included within the SAP calculations.
It is not a complete report of regulations compliance.

1a TER and DER

Fuel for main heating:Mains gas
Fuel factor:1.00 (mains gas)
Target Carbon Dioxide Emission Rate (TER) 19.20 kgCO₂/m²
Dwelling Carbon Dioxide Emission Rate (DER) 17.48 kgCO₂/m²OK

1b TFEE and DFEE

Target Fabric Energy Efficiency (TFEE)54.0 kWh/m²/yr
Dwelling Fabric Energy Efficiency (DFEE)46.1 kWh/m²/yrOK

2 Fabric U-values

Element	Average	Highest	
External wall	0.24 (max. 0.30)	0.24 (max. 0.70)	OK
Party wall	0.00 (max. 0.20)	-	OK
Floor	0.14 (max. 0.25)	0.14 (max. 0.70)	OK
Roof	0.09 (max. 0.20)	0.09 (max. 0.35)	OK
Openings	1.22 (max. 2.00)	1.40 (max. 3.30)	OK

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals: 5.00 (design value)
Maximum 10.0 OK

4 Heating efficiency

Main heating system: Boiler system with radiators or underfloor - Mains gas

Data from database

Vaillant ecoFIT sustain 830 VUW 306/6-3 (H-GB)

Combi boiler

Efficiency: 89.3% SEDBUK2009

Minimum: 88.0%

OK

Secondary heating system:

None

5 Cylinder insulation

Hot water storage No cylinder

6 Controls

Space heating controls: Time and temperature zone control OK

Hot water controls:

No cylinder

Boiler interlock

Yes

OK

7 Low energy lights

Percentage of fixed lights with low-energy fittings:100%
Minimum 75% OK

8 Mechanical ventilation

Not applicable

9 Summertime temperature

Overheating risk (Thames Valley): Not significant OK

Based on:

Overshading:

Average

Windows facing South East: 3.80 m², No overhang

Windows facing South West: 1.76 m², No overhang

Windows facing North West: 6.66 m², No overhang

Air change rate: 8.00 ach

Blinds/curtains:

None

10 Key features

Party wall U-value 0.00 W/m²K

Roof U-value 0.09 W/m²K

Door U-value 1.00 W/m²K

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

CALCULATION OF DWELLING EMISSIONS FOR REGULATIONS COMPLIANCE 09 Jan 2014

SAP 2012 WORKSHEET FOR New Build (As Designed) (Version 9.92, January 2014)
 CALCULATION OF DWELLING EMISSIONS FOR REGULATIONS COMPLIANCE 09 Jan 2014

1. Overall dwelling dimensions

	Area (m2)	Storey height (m)	Volume (m3)
Ground floor	37.2100 (1b)	2.3900 (2b)	88.9319 (1b) - (3b)
First floor	37.2100 (1c)	2.6000 (2c)	96.7460 (1c) - (3c)
Total floor area TFA = (1a)+(1b)+(1c)+(1d)+(1e)...(1n)	74.4200		(3a)+(3b)+(3c)+(3d)+(3e)...(3n) = 185.6779 (5)

2. Ventilation rate

	main heating	secondary heating	other	total	m3 per hour
Number of chimneys	0	0	0	0 * 40 =	0.0000 (6a)
Number of open flues	0	0	0	0 * 20 =	0.0000 (6b)
Number of intermittent fans				3 * 10 =	30.0000 (7a)
Number of passive vents				0 * 10 =	0.0000 (7b)
Number of flueless gas fires				0 * 40 =	0.0000 (7c)
Infiltration due to chimneys, flues and fans = (6a)+(6b)+(7a)+(7b)+(7c)				30.0000 / (5) =	0.1616 (8)
Pressure test					Yes
Measured/design AP50					5.0000
Infiltration rate					0.4116 (18)
Number of sides sheltered					2 (19)
Shelter factor			(20) = 1 - [0.075 x (19)] =		0.8500 (20)
Infiltration rate adjusted to include shelter factor			(21) = (18) x (20) =		0.3498 (21)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Wind speed	5.1000	5.0000	4.9000	4.4000	4.3000	3.8000	3.8000	3.7000	4.0000	4.3000	4.5000	4.7000 (22)
Wind factor	1.2750	1.2500	1.2250	1.1000	1.0750	0.9500	0.9500	0.9250	1.0000	1.0750	1.1250	1.1750 (22a)
Adj infilt rate												
Effective ac	0.4460	0.4373	0.4285	0.3848	0.3761	0.3323	0.3323	0.3236	0.3498	0.3761	0.3936	0.4111 (22b)
	0.5995	0.5956	0.5918	0.5740	0.5707	0.5552	0.5552	0.5524	0.5612	0.5707	0.5774	0.5845 (25)

3. Heat losses and heat loss parameter

Element	Gross m2	Openings m2	NetArea m2	U-value W/m2K	A x U W/K	K-value kJ/m2K	A x K kJ/K
Half Glazed Door			2.1000	1.0000	2.1000		(26a)
Windows (Uw = 1.20)			8.4400	1.1450	9.6641		(27)
Patio Door (Uw = 1.40)			3.7800	1.3258	5.0114		(27)
Ground Floor			37.2100	0.1400	5.2094	75.0000	2790.7500 (28a)
External Wall	86.3900	14.3200	72.0700	0.2400	17.2968	60.0000	4324.2000 (29a)
Cold Roof	37.2100		37.2100	0.0900	3.3489	9.0000	334.8900 (30)
Total net area of external elements Aum(A, m2)			160.8100				(31)
Fabric heat loss, W/K = Sum (A x U)				(26)...(30) + (32) =	42.6306		(33)
Party Wall 1			40.1900	0.0000	0.0000	45.0000	1808.5500 (32)
GF			58.1200			9.0000	523.0800 (32c)
FF			85.6400			9.0000	770.7600 (32c)
FF			37.2100			18.0000	669.7800 (32d)
GF			37.2100			18.0000	669.7800 (32e)
Heat capacity Cm = Sum(A x k)						(28)...(30) + (32) + (32a)...(32e) =	11891.7900 (34)
Thermal mass parameter (TMP = Cm / TFA) in kJ/m2K							159.7929 (35)
Thermal bridges (Sum(L x Psi) calculated using Appendix K)							8.4512 (36)
Total fabric heat loss						(33) + (36) =	51.0818 (37)

Ventilation heat loss calculated monthly (38)m = 0.33 x (25)m x (5)

(38)m	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Heat transfer coeff	36.7321	36.4954	36.2634	35.1737	34.9698	34.0207	34.0207	33.8450	34.3863	34.9698	35.3823	35.8135 (38)
Average = Sum(39)m / 12 =	87.8138	87.5772	87.3452	86.2555	86.0516	85.1025	85.1025	84.9267	85.4681	86.0516	86.4640	86.8952 (39)
												86.2545 (39)

HLP	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
HLP (average)	1.1800	1.1768	1.1737	1.1590	1.1563	1.1435	1.1435	1.1412	1.1485	1.1563	1.1618	1.1676 (40)
Days in month	31	28	31	30	31	30	31	31	30	31	30	31 (41)

4. Water heating energy requirements (kWh/year)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Assumed occupancy												2.3485 (42)
Average daily hot water use (litres/day)												89.9765 (43)
Daily hot water use	98.9741	95.3751	91.7760	88.1770	84.5779	80.9788	80.9788	84.5779	88.1770	91.7760	95.3751	98.9741 (44)
Energy conte	146.7758	128.3710	132.4674	115.4883	110.8138	95.6239	88.6096	101.6808	102.8952	119.9144	130.8959	142.1445 (45)

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

CALCULATION OF DWELLING EMISSIONS FOR REGULATIONS COMPLIANCE 09 Jan 2014

Energy content (annual)												Total = Sum(45)m =	1415.6806 (45)
Distribution loss (46)m = 0.15 x (45)m													
	22.0164	19.2557	19.8701	17.3232	16.6221	14.3436	13.2914	15.2521	15.4343	17.9872	19.6344	21.3217	(46)
Water storage loss:													
Total storage loss	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	(56)
If cylinder contains dedicated solar storage	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	(57)
Combi loss	1.6706	1.4080	1.3981	1.1711	1.0778	0.8905	0.8252	0.9890	1.0434	1.2656	1.4357	1.6179	(61)
Total heat required for water heating calculated for each month	148.4464	129.7790	133.8655	116.6594	111.8916	96.5144	89.4348	102.6698	103.9386	121.1800	132.3316	143.7624	(62)
Solar input	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	(63)
Solar input (sum of months) = Sum(63)m =												0.0000 (63)	
Output from w/h	148.4464	129.7790	133.8655	116.6594	111.8916	96.5144	89.4348	102.6698	103.9386	121.1800	132.3316	143.7624	(64)
Total per year (kWh/year) = Sum(64)m =												1430.4735 (64)	
Heat gains from water heating, kWh/month	49.2206	43.0354	44.3949	38.6926	37.1150	32.0176	29.6690	34.0561	34.4735	40.1879	43.8818	47.6675	(65)

5. Internal gains (see Table 5 and 5a)

Metabolic gains (Table 5), Watts													
(66)m	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	(66)
Lighting gains (calculated in Appendix L, equation L9 or L9a), also see Table 5	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	(67)
Appliances gains (calculated in Appendix L, equation L13 or L13a), also see Table 5	19.1919	17.0461	13.8628	10.4950	7.8452	6.6232	7.1566	9.3025	12.4857	15.8535	18.5034	19.7253	(67)
Cooking gains (calculated in Appendix L, equation L15 or L15a), also see Table 5	207.3859	209.5379	204.1149	192.5700	177.9965	164.2996	155.1492	152.9971	158.4201	169.9651	184.5385	198.2355	(68)
Pumps, fans	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	(69)
Losses e.g. evaporation (negative values) (Table 5)	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	(70)
Water heating gains (Table 5)	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	(71)
Total internal gains	66.1567	64.0407	59.6706	53.7398	49.8858	44.4688	39.8777	45.7743	47.8799	54.0160	60.9470	64.0693	(72)
	353.9618	351.8520	338.8756	318.0320	296.9548	276.6189	263.4107	269.3012	280.0130	301.0619	325.2161	343.2573	(73)

6. Solar gains

[Jan]			Area	Solar flux	g	FF	Access	Gains					
			m ²	Table 6a	Specific data	Specific data	factor	W					
				W/m ²	or Table 6b	or Table 6c	Table 6d						
Southeast			3.8000	36.7938	0.6300	0.7000	0.7700	42.7298 (77)					
Southwest			1.7600	36.7938	0.6300	0.7000	0.7700	19.7906 (79)					
Northwest			2.8800	11.2829	0.6300	0.7000	0.7700	9.9309 (81)					
Northwest			3.7800	11.2829	0.6300	0.7000	0.7700	13.0342 (81)					
Solar gains	85.4855	153.2415	229.9332	318.8599	388.1481	398.9763	378.9814	325.2048	260.4002	174.8275	103.7811	72.2589	(83)
Total gains	439.4473	505.0935	568.8089	636.8919	685.1028	675.9552	642.3921	594.5059	540.4132	475.8894	428.9972	415.5162	(84)

7. Mean internal temperature (heating season)

Temperature during heating periods in the living area from Table 9, Th1 (C)												21.0000 (85)	
Utilisation factor for gains for living area, nil,m (see Table 9a)													
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
tau	37.6168	37.7185	37.8186	38.2964	38.3871	38.8153	38.8153	38.8956	38.6492	38.3871	38.2040	38.0145	
alpha	3.5078	3.5146	3.5212	3.5531	3.5591	3.5877	3.5877	3.5930	3.5766	3.5591	3.5469	3.5343	
util living area	0.9897	0.9824	0.9662	0.9247	0.8369	0.6913	0.5446	0.5988	0.8143	0.9476	0.9832	0.9915	(86)
MIT	19.1925	19.3976	19.7418	20.1989	20.6000	20.8627	20.9565	20.9386	20.7356	20.2174	19.6269	19.1582	(87)
Th 2	19.9361	19.9386	19.9411	19.9529	19.9551	19.9654	19.9654	19.9673	19.9615	19.9551	19.9507	19.9460	(88)
util rest of house	0.9874	0.9785	0.9582	0.9058	0.7946	0.6115	0.4319	0.4864	0.7510	0.9307	0.9787	0.9896	(89)
MIT 2	17.5259	17.8252	18.3244	18.9816	19.5265	19.8527	19.9422	19.9316	19.7153	19.0203	18.1685	17.4821	(90)
Living area fraction												fLA = Living area / (4) =	
MIT	18.0700	18.3386	18.7872	19.3791	19.8770	20.1825	20.2734	20.2604	20.0485	19.4111	18.6447	18.0294	(92)
Temperature adjustment												-0.1500	
adjusted MIT	17.9200	18.1886	18.6372	19.2291	19.7270	20.0325	20.1234	20.1104	19.8985	19.2611	18.4947	17.8794	(93)

8. Space heating requirement

Utilisation	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
	0.9809	0.9692	0.9450	0.8895	0.7838	0.6171	0.4501	0.5031	0.7465	0.9159	0.9697	0.9840	(94)
Useful gains	431.0624	489.5232	537.4985	566.5310	537.0164	416.9326	289.1334	299.1112	403.4095	435.8647	416.0117	408.8759	(95)
Ext temp.	4.3000	4.9000	6.5000	8.9000	11.7000	14.6000	16.6000	16.4000	14.1000	10.6000	7.1000	4.2000	(96)
Heat loss rate W	1196.0288	1163.7821	1060.1257	890.9390	690.7401	462.3211	299.8497	315.1120	495.5856	745.3046	985.2284	1188.6764	(97)
Month fracti	1.0000	1.0000	1.0000	1.0000	1.0000	0.0000	0.0000	0.0000	0.0000	1.0000	1.0000	1.0000	(97a)
Space heating kWh	569.1350	453.1020	388.8347	233.5737	114.3704	0.0000	0.0000	0.0000	0.0000	230.2233	409.8361	580.1716	(98)
Space heating												2979.2468 (98)	
Space heating per m ²												(98) / (4) = 40.0329 (99)	

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

CALCULATION OF DWELLING EMISSIONS FOR REGULATIONS COMPLIANCE 09 Jan 2014

8c. Space cooling requirement

Not applicable

9a. Energy requirements - Individual heating systems, including micro-CHP

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
Fraction of space heat from secondary/supplementary system (Table 11)													0.0000 (201)
Fraction of space heat from main system(s)													1.0000 (202)
Efficiency of main space heating system 1 (in %)													90.2000 (206)
Efficiency of secondary/supplementary heating system, %													0.0000 (208)
Space heating requirement													3302.9344 (211)
Space heating requirement	569.1350	453.1020	388.8347	233.5737	114.3704	0.0000	0.0000	0.0000	0.0000	230.2233	409.8361	580.1716	(98)
Space heating efficiency (main heating system 1)	90.2000	90.2000	90.2000	90.2000	90.2000	0.0000	0.0000	0.0000	0.0000	90.2000	90.2000	90.2000	(210)
Space heating fuel (main heating system)	630.9701	502.3304	431.0806	258.9509	126.7965	0.0000	0.0000	0.0000	0.0000	255.2365	454.3637	643.2057	(211)
Water heating requirement	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	(215)
Water heating requirement	148.4464	129.7790	133.8655	116.6594	111.8916	96.5144	89.4348	102.6698	103.9386	121.1800	132.3316	143.7624	(64)
Efficiency of water heater (217)m	86.8972	86.6552	86.1465	84.9983	82.6873	76.2000	76.2000	76.2000	76.2000	84.8257	86.3287	76.2000	(216)
Fuel for water heating, kWh/month	170.8298	149.7649	155.3928	137.2491	135.3190	126.6593	117.3684	134.7372	136.4023	142.8577	153.2881	165.1969	(219)
Water heating fuel used													1725.0657 (219)
Annual totals kWh/year													
Space heating fuel - main system													3302.9344 (211)
Space heating fuel - secondary													0.0000 (215)
Electricity for pumps and fans:													
central heating pump													30.0000 (230c)
main heating flue fan													45.0000 (230e)
Total electricity for the above, kWh/year													75.0000 (231)
Electricity for lighting (calculated in Appendix L)													338.9354 (232)
Total delivered energy for all uses													5441.9355 (238)

12a. Carbon dioxide emissions - Individual heating systems including micro-CHP

	Energy kWh/year	Emission factor kg CO2/kWh	Emissions kg CO2/year	
Space heating - main system 1	3302.9344	0.2160	713.4338	(261)
Space heating - secondary	0.0000	0.0000	0.0000	(263)
Water heating (other fuel)	1725.0657	0.2160	372.6142	(264)
Space and water heating			1086.0480	(265)
Pumps and fans	75.0000	0.5190	38.9250	(267)
Energy for lighting	338.9354	0.5190	175.9074	(268)
Total CO2, kg/year			1300.8805	(272)
Dwelling Carbon Dioxide Emission Rate (DER)			17.4800	(273)

16 CO2 EMISSIONS ASSOCIATED WITH APPLIANCES AND COOKING AND SITE-WIDE ELECTRICITY GENERATION TECHNOLOGIES

	DER	TFA	N	EF	
DER					17.4800 ZC1
Total Floor Area		74.4200			
Assumed number of occupants			2.3485		
CO2 emission factor in Table 12 for electricity displaced from grid				0.5190	
CO2 emissions from appliances, equation (L14)					16.5134 ZC2
CO2 emissions from cooking, equation (L16)					2.3564 ZC3
Total CO2 emissions					36.3498 ZC4
Residual CO2 emissions offset from biofuel CHP					0.0000 ZC5
Additional allowable electricity generation, kWh/m ² /year					0.0000 ZC6
Resulting CO2 emissions offset from additional allowable electricity generation					0.0000 ZC7
Net CO2 emissions					36.3498 ZC8

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

CALCULATION OF TARGET EMISSIONS 09 Jan 2014

SAP 2012 WORKSHEET FOR New Build (As Designed) (Version 9.92, January 2014)
CALCULATION OF TARGET EMISSIONS 09 Jan 2014

1. Overall dwelling dimensions

	Area (m ²)	Storey height (m)	Volume (m ³)
Ground floor	37.2100 (1b)	2.3900 (2b)	88.9319 (1b) - (3b)
First floor	37.2100 (1c)	2.6000 (2c)	96.7460 (1c) - (3c)
Total floor area TFA = (1a)+(1b)+(1c)+(1d)+(1e)...(1n)	74.4200		(4)
Dwelling volume			(3a)+(3b)+(3c)+(3d)+(3e)...(3n) = 185.6779 (5)

2. Ventilation rate

	main heating	secondary heating	other	total	m ³ per hour							
Number of chimneys	0	0	0	0 * 40 =	0.0000 (6a)							
Number of open flues	0	0	0	0 * 20 =	0.0000 (6b)							
Number of intermittent fans				3 * 10 =	30.0000 (7a)							
Number of passive vents				0 * 10 =	0.0000 (7b)							
Number of flueless gas fires				0 * 40 =	0.0000 (7c)							
Infiltration due to chimneys, flues and fans = (6a)+(6b)+(7a)+(7b)+(7c) =				30.0000 / (5) =	0.1616 (8)							
Pressure test					Yes							
Measured/design AP50					5.0000							
Infiltration rate					0.4116 (18)							
Number of sides sheltered					2 (19)							
Shelter factor			(20) = 1 - [0.075 x (19)] =		0.8500 (20)							
Infiltration rate adjusted to include shelter factor			(21) = (18) x (20) =		0.3498 (21)							
Wind speed	Jan 5.1000	Feb 5.0000	Mar 4.9000	Apr 4.4000	May 4.3000	Jun 3.8000	Jul 3.8000	Aug 3.7000	Sep 4.0000	Oct 4.3000	Nov 4.5000	Dec 4.7000 (22)
Wind factor	1.2750	1.2500	1.2250	1.1000	1.0750	0.9500	0.9500	0.9250	1.0000	1.0750	1.1250	1.1750 (22a)
Adj infilt rate	0.4460	0.4373	0.4285	0.3848	0.3761	0.3323	0.3323	0.3236	0.3498	0.3761	0.3936	0.4111 (22b)
Effective ac	0.5995	0.5956	0.5918	0.5740	0.5707	0.5552	0.5552	0.5524	0.5612	0.5707	0.5774	0.5845 (25)

3. Heat losses and heat loss parameter

Element	Gross m ²	Openings m ²	NetArea m ²	U-value W/m ² K	A x U W/K	K-value kJ/m ² K	A x K kJ/K					
TER Semi-glazed door			2.1000	1.2000	2.5200		(26a)					
TER Opening Type (Uw = 1.40)			12.2200	1.3258	16.2008		(27)					
Ground Floor			37.2100	0.1300	4.8373		(28a)					
External Wall	86.3900	14.3200	72.0700	0.1800	12.9726		(29a)					
Cold Roof	37.2100		37.2100	0.1300	4.8373		(30)					
Total net area of external elements Aum(A, m ²)			160.8100				(31)					
Fabric heat loss, W/K = Sum (A x U)					(26)...(30) + (32) =	41.3680	(33)					
Thermal mass parameter (TMP = Cm / TFA) in kJ/m ² K							250.0000 (35)					
Thermal bridges (Sum(L x Psi) calculated using Appendix K)							9.7290 (36)					
Total fabric heat loss							(33) + (36) = 51.0970 (37)					
Ventilation heat loss calculated monthly (38)m = 0.33 x (25)m x (5)												
Heat transfer coeff	Jan 36.7321	Feb 36.4954	Mar 36.2634	Apr 35.1737	May 34.9698	Jun 34.0207	Jul 34.0207	Aug 33.8450	Sep 34.3863	Oct 34.9698	Nov 35.3823	Dec 35.8135 (38)
Average = Sum(39)m / 12 =	87.8290	87.5924	87.3604	86.2707	86.0668	85.1177	85.1177	84.9419	85.4833	86.0668	86.4792	86.9104 (39)
HLP	Jan 1.1802	Feb 1.1770	Mar 1.1739	Apr 1.1592	May 1.1565	Jun 1.1437	Jul 1.1437	Aug 1.1414	Sep 1.1487	Oct 1.1565	Nov 1.1620	Dec 1.1678 (40)
HLP (average)												1.1592 (40)
Days in month	31	28	31	30	31	30	31	31	30	31	30	31 (41)

4. Water heating energy requirements (kWh/year)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Assumed occupancy												2.3485 (42)
Average daily hot water use (litres/day)												89.9765 (43)
Daily hot water use	98.9741	95.3751	91.7760	88.1770	84.5779	80.9788	80.9788	84.5779	88.1770	91.7760	95.3751	98.9741 (44)
Energy content (annual)	146.7758	128.3710	132.4674	115.4883	110.8138	95.6239	88.6096	101.6808	102.8952	119.9144	130.8959	142.1445 (45)
Distribution loss (46)m = 0.15 x (45)m	22.0164	19.2557	19.8701	17.3232	16.6221	14.3436	13.2914	15.2521	15.4343	17.9872	19.6344	21.3217 (46)
Water storage loss:												
Total storage loss	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000 (56)
If cylinder contains dedicated solar storage												

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

CALCULATION OF TARGET EMISSIONS 09 Jan 2014

Combi loss	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	(57)
Total heat required for water heating calculated for each month	50.4361	43.8987	46.7681	43.4845	43.1000	39.9348	41.2659	43.1000	43.4845	46.7681	47.0343	50.4361	61										
Solar input	197.2119	172.2697	179.2355	158.9728	153.9138	135.5586	129.8755	144.7808	146.3797	166.6825	177.9302	192.5807	(62)										
Output from w/h	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	(63)										
Heat gains from water heating, kWh/month	197.2119	172.2697	179.2355	158.9728	153.9138	135.5586	129.8755	144.7808	146.3797	166.6825	177.9302	192.5807	(64)										
	61.4120	53.6580	55.7374	49.2710	47.6206	41.7786	39.7792	44.5839	45.0838	51.5636	55.2815	59.8721	(65)										

5. Internal gains (see Table 5 and 5a)

Metabolic gains (Table 5), Watts	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	(66)
(66)m	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	117.4242	(66)
Lighting gains (calculated in Appendix L, equation L9 or L9a), also see Table 5	19.1919	17.0461	13.8628	10.4950	7.8452	6.6232	7.1566	9.3025	12.4857	15.8535	18.5034	19.7253	(67)
Appliances gains (calculated in Appendix L, equation L13 or L13a), also see Table 5	207.3859	209.5379	204.1149	192.5700	177.9965	164.2996	155.1492	152.9971	158.4201	169.9651	184.5385	198.2355	(68)
Cooking gains (calculated in Appendix L, equation L15 or L15a), also see Table 5	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	34.7424	(69)
Pumps, fans	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	3.0000	(70)
Losses e.g. evaporation (negative values) (Table 5)	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	-93.9394	(71)
Water heating gains (Table 5)	82.5430	79.8483	74.9159	68.4319	64.0062	58.0259	53.4666	59.9245	62.6164	69.3059	76.7798	80.4732	(72)
Total internal gains	370.3481	367.6596	354.1209	332.7242	311.0751	290.1759	276.9997	283.4514	294.7495	316.3517	341.0490	359.6613	(73)

6. Solar gains

[Jan]	Area	Solar flux	g	FF	Access	Gains							
	m2	Table 6a	Specific data	Specific data	factor	W							
		W/m2	or Table 6b	or Table 6c	Table 6d								
Southeast	3.8000	36.7938	0.6300	0.7000	0.7700	42.7298 (77)							
Southwest	1.7600	36.7938	0.6300	0.7000	0.7700	19.7906 (79)							
Northwest	6.6600	11.2829	0.6300	0.7000	0.7700	22.9651 (81)							
Solar gains	85.4855	153.2415	229.9332	318.8599	388.1481	398.9763	378.9814	325.2048	260.4002	174.8275	103.7811	72.2589	(83)
Total gains	455.8336	520.9010	584.0541	651.5841	699.2232	689.1523	655.9811	608.6561	555.1497	491.1792	444.8300	431.9202	(84)

7. Mean internal temperature (heating season)

Temperature during heating periods in the living area from Table 9, Th1 (C)													21.0000 (85)
Utilisation factor for gains for living area, nil,m (see Table 9a)	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
tau	58.8422	59.0012	59.1579	59.9051	60.0470	60.7166	60.7166	60.8422	60.4569	60.0470	59.7607	59.4642	
alpha	4.9228	4.9334	4.9439	4.9937	5.0031	5.0478	5.0478	5.0561	5.0305	5.0031	4.9840	4.9643	
util living area	0.9978	0.9954	0.9882	0.9620	0.8843	0.7239	0.5560	0.6157	0.8584	0.9770	0.9955	0.9983	(86)
MIT	19.7300	19.8801	20.1335	20.4746	20.7705	20.9420	20.9876	20.9798	20.8570	20.4766	20.0440	19.7058	(87)
Th 2	19.9359	19.9384	19.9410	19.9527	19.9550	19.9653	19.9653	19.9672	19.9613	19.9550	19.9505	19.9458	(88)
util rest of house	0.9971	0.9938	0.9838	0.9473	0.8400	0.6321	0.4329	0.4904	0.7887	0.9653	0.9937	0.9978	(89)
MIT 2	18.2469	18.4677	18.8375	19.3323	19.7276	19.9263	19.9607	19.9588	19.8444	19.3439	18.7162	18.2186	(90)
Living area fraction	fLA = Living area / (4) =												0.3265 (91)
MIT	18.7312	18.9289	19.2607	19.7053	20.0682	20.2580	20.2960	20.2922	20.1751	19.7137	19.1497	18.7042	(92)
Temperature adjustment													0.0000
adjusted MIT	18.7312	18.9289	19.2607	19.7053	20.0682	20.2580	20.2960	20.2922	20.1751	19.7137	19.1497	18.7042	(93)

8. Space heating requirement

Utilisation	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
	0.9958	0.9916	0.9801	0.9430	0.8455	0.6599	0.4734	0.5316	0.8052	0.9618	0.9917	0.9968	(94)
Useful gains	453.9287	516.5251	572.4227	614.4406	591.1946	454.7577	310.5365	323.5322	446.9807	472.3966	441.1442	430.5246	(95)
Ext temp.	4.3000	4.9000	6.5000	8.9000	11.7000	14.6000	16.6000	16.4000	14.1000	10.6000	7.1000	4.2000	(96)
Heat loss rate W	1267.4772	1228.8260	1114.7775	932.1773	720.2205	481.5926	314.5943	330.6084	519.3153	784.3899	1042.0517	1260.5640	(97)
Month fracti	1.0000	1.0000	1.0000	1.0000	1.0000	0.0000	0.0000	0.0000	0.0000	1.0000	1.0000	1.0000	(97a)
Space heating kWh	605.2800	478.6662	403.5119	228.7704	95.9952	0.0000	0.0000	0.0000	0.0000	232.1230	432.6534	617.5492	(98)
Space heating													3094.5494 (98)
Space heating per m2													(98) / (4) = 41.5822 (99)

8c. Space cooling requirement

Not applicable

FULL SAP CALCULATION PRINTOUT

Calculation Type: New Build (As Designed)

CALCULATION OF TARGET EMISSIONS 09 Jan 2014

9a. Energy requirements - Individual heating systems, including micro-CHP

Fraction of space heat from secondary/supplementary system (Table 11)													0.0000 (201)
Fraction of space heat from main system(s)													1.0000 (202)
Efficiency of main space heating system 1 (in %)													93.4000 (206)
Efficiency of secondary/supplementary heating system, %													0.0000 (208)
Space heating requirement													3313.2221 (211)
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
Space heating requirement	605.2800	478.6662	403.5119	228.7704	95.9952	0.0000	0.0000	0.0000	0.0000	232.1230	432.6534	617.5492	(98)
Space heating efficiency (main heating system 1)	93.4000	93.4000	93.4000	93.4000	93.4000	0.0000	0.0000	0.0000	0.0000	93.4000	93.4000	93.4000	(210)
Space heating fuel (main heating system)	648.0514	512.4906	432.0256	244.9362	102.7786	0.0000	0.0000	0.0000	0.0000	248.5257	463.2263	661.1876	(211)
Water heating requirement	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	(215)
Water heating requirement	197.2119	172.2697	179.2355	158.9728	153.9138	135.5586	129.8755	144.7808	146.3797	166.6825	177.9302	192.5807	(64)
Efficiency of water heater (217)m	87.6895	87.4878	87.0331	85.9668	83.9007	80.3000	80.3000	80.3000	80.3000	85.8851	87.2037	80.3000	(216)
Fuel for water heating, kWh/month	224.8980	196.9072	205.9395	184.9235	183.4475	168.8152	161.7379	180.2998	182.2910	194.0762	204.0397	219.4012	(219)
Water heating fuel used													2306.7768 (219)
Annual totals kWh/year													
Space heating fuel - main system													3313.2221 (211)
Space heating fuel - secondary													0.0000 (215)
Electricity for pumps and fans:													
central heating pump													30.0000 (230c)
main heating flue fan													45.0000 (230e)
Total electricity for the above, kWh/year													75.0000 (231)
Electricity for lighting (calculated in Appendix L)													338.9354 (232)
Total delivered energy for all uses													6033.9343 (238)

12a. Carbon dioxide emissions - Individual heating systems including micro-CHP

	Energy kWh/year	Emission factor kg CO2/kWh	Emissions kg CO2/year
Space heating - main system 1	3313.2221	0.2160	715.6560 (261)
Space heating - secondary	0.0000	0.0000	0.0000 (263)
Water heating (other fuel)	2306.7768	0.2160	498.2638 (264)
Space and water heating			1213.9198 (265)
Pumps and fans	75.0000	0.5190	38.9250 (267)
Energy for lighting	338.9354	0.5190	175.9074 (268)
Total CO2, kg/m2/year			1428.7522 (272)
Emissions per m2 for space and water heating			16.3117 (272a)
Fuel factor (mains gas)			1.0000
Emissions per m2 for lighting			2.3637 (272b)
Emissions per m2 for pumps and fans			0.5230 (272c)
Target Carbon Dioxide Emission Rate (TER) = (16.3117 * 1.00) + 2.3637 + 0.5230, rounded to 2 d.p.			19.2000 (273)

U-VALUE CALCULATOR REPORT

Property Reference	007818 - Plot 137		Issued on Date	15/03/2021
Assessment Reference	Rev A	Prop Type Ref	007818-SAP-2328-Semi-MT	
Project	Plot 137			
Calculation Type	New Build (As Designed)			

SAP Rating	84 B	DER	17.48	TER	19.20
Environmental	87 B	% DER<TER	8.95		
CO ₂ Emissions (t/year)	1.08	DFEE	46.10	TFEE	54.05
General Requirements Compliance	Pass	% DFEE<TFEE	14.70		

Assessor Details	Mr. Paul Bainbridge, Paul Bainbridge, Tel: 01904 674890, paul.bainbridge@thefesgroup.com	Assessor ID	p717-0001
Client	Larkfleet Group		

Building Elements

Roof 007818 - Cold Roof

Roof Type: Pitched Roof, insulated flat ceiling

Layer	Description	Thickness (mm)	Conductivity (W/m ² K)	Resistance (m ² K/W)	Fraction (%)
Ext surface				0.0400	
Layer 1	Standard cavity Main construction Corrections - Cavity Unventilated, Emissivity: Normal	50	0.3125	0.1600	100.00
Layer 2	Crown Loft Roll 40 Main construction Corrections - Air Gap: Level 1, Fasteners: None or plastic	150	0.0400	3.7500	100.00
Layer 3	Crown Loft Roll 40 Main construction Corrections - Air Gap: Level 1, Fasteners: None or plastic	150	0.0400	3.7500	100.00
Layer 4	Crown Loft Roll 40 Main construction Corrections - Air Gap: Level 1, Fasteners: None or plastic	150	0.0400	3.7500	100.00
Layer 5	Plasterboard, standard Main construction	12.5	0.2100	0.0595	100.00
Int surface				0.1000	

Total resistance: Upper limit = 11.610 m² K/W Lower limit = 11.610 m² K/W Average = 11.610 m² K/W
Total correction = 0.0031 m² K/W U-value (unrounded) = 0.09 W/m² K

Unheated space: None

Total thickness: 513 mm

U-value: 0.09 W/m² K

Kappa: n/a

U-VALUE CALCULATOR REPORT

Property Reference	007818 - Plot 137		Issued on Date	15/03/2021
Assessment Reference	Rev A	Prop Type Ref	007818-SAP-2328-Semi-MT	
Project	Plot 137			
Calculation Type	New Build (As Designed)			

SAP Rating	84 B	DER	17.48	TER	19.20
Environmental	87 B	% DER<TER	8.95		
CO ₂ Emissions (t/year)	1.08	DFEE	46.10	TFEE	54.05
General Requirements Compliance	Pass	% DFEE<TFEE	14.70		

Assessor Details	Mr. Paul Bainbridge, Paul Bainbridge, Tel: 01904 674890, paul.bainbridge@thefesgroup.com	Assessor ID	p717-0001
------------------	--	-------------	-----------

Client	Larkfleet Group
--------	-----------------

Building Elements

Wall 007818 - External Wall

Wall Type: Standard Wall

Layer	Description	Thickness (mm)	Conductivity (W/m ² K)	Resistance (m ² K/W)	Fraction (%)
Ext surface				0.0400	
Layer 1	Brick, outer leaf				
	Main construction	100	0.7700	0.1299	82.81
	Main construction	100	0.9407	0.1063	17.19
Layer 2	URSA Cavity BATT 32				
	Main construction	100	0.0320	3.1250	100.00
	Corrections - Air Gap: Level 1, Fasteners: None or plastic				
Layer 3	Thermalite Shield				
	Main construction	100	0.1500	0.6667	93.43
	Main construction	100	0.8803	0.1136	6.57
	Corrections - Air Gap: Level 1, Fasteners: None or plastic				
Layer 4	airspace/plaster dabs				
	Main construction	15	0.0882	0.1700	80.00
	Main construction	15	0.0882	0.1700	20.00
	Corrections - Cavity Unventilated, Emissivity: Normal				
Layer 5	Plasterboard, standard				
	Main construction	12.5	0.2100	0.0595	100.00
Int surface				0.1300	

Total resistance:	Upper limit = 4.276 m ² K/W	Lower limit = 4.155 m ² K/W	Average = 4.215 m ² K/W
	Total correction = 0.0056 m ² K/W	U-value (unrounded) = 0.24 W/m ² K	

Unheated space: None

Total thickness: 328 mm

U-value: 0.24 W/m² K

Kappa: n/a

U-VALUE CALCULATOR REPORT

Property Reference	007818 - Plot 137		Issued on Date	15/03/2021
Assessment Reference	Rev A	Prop Type Ref	007818-SAP-2328-Semi-MT	
Project	Plot 137			
Calculation Type	New Build (As Designed)			

SAP Rating	84 B	DER	17.48	TER	19.20
Environmental	87 B	% DER<TER	8.95		
CO ₂ Emissions (t/year)	1.08	DFEE	46.10	TFEE	54.05
General Requirements Compliance	Pass	% DFEE<TFEE	14.70		

Assessor Details	Mr. Paul Bainbridge, Paul Bainbridge, Tel: 01904 674890, paul.bainbridge@thefesgroup.com	Assessor ID	p717-0001
------------------	--	-------------	-----------

Client	Larkfleet Group
--------	-----------------

Building Elements

Floor 007818 - Ground Floor

Floor Type: Suspended Floor

Area = 37.21 m², Perimeter = 17.30 m, Wall thickness = 275.00 mm, Soil: Unknown

Depth of underfloor space below ground: 0.200 m Floor wind shielding: Average (suburban)

Floor height above ground: h = 0.200 m

U-value of walls above ground: U_w = 1.500 m

Ventilation openings per perimeter length: e = 0.0015 %

Mean wind speed: v = 5.000 m/s

Resistance on solum: R_g = 0.000 m²K/W

Layer	Description	Thickness (mm)	Conductivity (W/m ² K)	Resistance (m ² K/W)	Fraction (%)
Ext surface				0.1700	
Layer 1	Standard cavity				
	Main construction	50	0.2381	0.2100	50.00
	Main construction	50	1.3500	0.0370	50.00
	Corrections - Cavity Unventilated, Emissivity: Normal				
Layer 2	Blockwork, dense				
	Main construction	100	1.5900	0.0629	77.78
	Main construction	100	1.3500	0.0741	22.22
Layer 3	Celotex XR4000				
	Main construction	120	0.0220	5.4545	100.00
	Corrections - Air Gap: Level 1, Fasteners: None or plastic				
Layer 4	Screed				
	Main construction	75	1.1500	0.0652	100.00
Int surface				0.1700	

Total resistance: Upper limit = 6.047 m² K/W Lower limit = 5.988 m² K/W Average = 6.018 m² K/W

Total correction = 0.0082 m² K/W

U-value (unrounded) = 0.14 W/m² K

Unheated space: None

Total thickness: 345 mm

U-value: 0.14 W/m² K

Kappa: n/a

BASIC COMPLIANCE REPORT

Calculation Type: New Build (As Designed)

Property Reference	007818 - Plot 137	Issued on Date	15/03/2021
Assessment Reference	Rev A	Prop Type Ref	007818-SAP-2328-Semi-MT
Property	Plot 137		

SAP Rating	84 B	DER	17.48	TER	19.20
Environmental	87 B	% DER<TER	8.95		
CO₂ Emissions (t/year)	1.08	DFEE	46.10	TFEE	54.05
General Requirements Compliance	Pass	% DFEE<TFEE	14.70		

Assessor Details	Mr. Paul Bainbridge, Paul Bainbridge, Tel: 01904 674890, paul.bainbridge@thefesgroup.com	Assessor ID	p717-0001
Client	Larkfleet Group		

SUMMARY FOR INPUT DATA FOR New Build (As Designed)

Criterion 1 – Achieving the TER and TFEE rate

1a TER and DER

Fuel for main heating	Mains gas		
Fuel factor	1.00 (mains gas)		
Target Carbon Dioxide Emission Rate (TER)	19.20	kgCO ₂ /m ²	
Dwelling Carbon Dioxide Emission Rate (DER)	17.48	kgCO ₂ /m ²	Pass
	-1.72 (-9.0%)	kgCO ₂ /m ²	

1b TFEE and DFEE

Target Fabric Energy Efficiency (TFEE)	54.05	kWh/m ² /yr	
Dwelling Fabric Energy Efficiency (DFEE)	46.10	kWh/m ² /yr	
	-7.9 (-14.6%)	kWh/m ² /yr	Pass

Criterion 2 – Limits on design flexibility

Limiting Fabric Standards

2 Fabric U-values

Element	Average	Highest	
External wall	0.24 (max. 0.30)	0.24 (max. 0.70)	Pass
Party wall	0.00 (max. 0.20)	-	Pass
Floor	0.14 (max. 0.25)	0.14 (max. 0.70)	Pass
Roof	0.09 (max. 0.20)	0.09 (max. 0.35)	Pass
Openings	1.22 (max. 2.00)	1.40 (max. 3.30)	Pass

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals	5.00 (design value)	
Maximum	10.0	Pass

Limiting System Efficiencies

4 Heating efficiency

BASIC COMPLIANCE REPORT

Calculation Type: New Build (As Designed)

Main heating system	Boiler system with radiators or underfloor - Mains gas Data from database Vaillant ecoFIT sustain 830 VUW 306/6-3 (H-GB) Combi boiler Efficiency: 89.3% SEDBUK2009 Minimum: 88.0%	Pass
Secondary heating system	None	

5 Cylinder insulation

Hot water storage	No cylinder	
-------------------	-------------	--

6 Controls

Space heating controls	Time and temperature zone control	Pass
Hot water controls	No cylinder	
Boiler interlock	Yes	Pass

7 Low energy lights

Percentage of fixed lights with low-energy fittings	100	%	
Minimum	75	%	Pass

8 Mechanical ventilation

Not applicable

Criterion 3 – Limiting the effects of heat gains in summer

9 Summertime temperature

Overheating risk (Thames Valley)	Not significant	Pass
Based on:		
Overshading	Average	
Windows facing South East	3.80 m ² , No overhang	
Windows facing South West	1.76 m ² , No overhang	
Windows facing North West	6.66 m ² , No overhang	
Air change rate	8.00 ach	
Blinds/curtains	None	

Criterion 4 – Building performance consistent with DER and DFEE rate

Party Walls

Type	U-value	W/m ² K	
Filled Cavity with Edge Sealing	0.00	W/m ² K	Pass

Air permeability and pressure testing

3 Air permeability

Air permeability at 50 pascals	5.00 (design value)	
Maximum	10.0	Pass

10 Key features

Party wall U-value	0.00	W/m ² K
Roof U-value	0.09	W/m ² K
Door U-value	1.00	W/m ² K

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

Property Reference	007818 - Plot 137		Issued on Date	15/03/2021	
Assessment Reference	Rev A	Prop Type Ref	007818-SAP-2328-Semi-MT		
Property	Plot 137				
SAP Rating	84 B	DER	17.48	TER	19.20
Environmental	87 B	% DER<TER	8.95		
CO ₂ Emissions (t/year)	1.08	DFEE	46.10	TFEE	54.05
General Requirements Compliance	Pass	% DFEE<TFEE	14.70		
Assessor Details	Mr. Paul Bainbridge, Paul Bainbridge, Tel: 01904 674890, paul.bainbridge@thefesgroup.com			Assessor ID	p717-0001
Client	Larkfleet Group				

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	South East
Property Tenure	Unknown
Transaction Type	New dwelling
Terrain Type	Suburban
1.0 Property Type	House, End-Terrace
2.0 Number of Storeys	2
3.0 Date Built	2020
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown

6.0 Measurements

	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground Floor:	17.30 m	37.21 m ²	2.39 m
1st Storey:	17.30 m	37.21 m ²	2.60 m

7.0 Living Area m²

8.0 Thermal Mass Parameter
 Thermal Mass
 kJ/m²K

9.0 External Walls

Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area (m ²)	Nett Area (m ²)
External Wall	Cavity Wall	Cavity wall : plasterboard on dabs, AAC block, filled cavity, any outside structure	0.24	60.00	86.39	72.07

9.1 Party Walls

Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Area (m ²)
Party Wall 1	Filled Cavity with Edge Sealing	Plasterboard on dabs mounted on cement render on both sides, AAC blocks, cavity	0.00	45.00	40.19

9.2 Internal Walls

Description	Construction	Kappa (kJ/m ² K)	Area (m ²)
GF	Plasterboard on timber frame	9.00	58.12
FF	Plasterboard on timber frame	9.00	85.64

10.0 External Roofs

Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area (m ²)	Nett Area (m ²)
Cold Roof	External Plane Roof	Plasterboard, insulated at ceiling level	0.09	9.00	37.21	37.21

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

10.2 Internal Ceilings

Description	Construction	Kappa (kJ/m ² K)	Area (m ²)
GF	Plasterboard ceiling, carpeted chipboard floor	9.00	37.21

11.0 Heat Loss Floors

Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Area (m ²)
Ground Floor	Ground Floor - Solid	Suspended concrete floor, carpeted	0.14	75.00	37.21

11.2 Internal Floors

Description	Construction	Kappa (kJ/m ² K)	Area (m ²)
FF	Plasterboard ceiling, carpeted chipboard floor	18.00	37.21

12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Argon Filled	G-value	Frame Type	Frame Factor	U Value (W/m ² K)
Half Glazed Door	Manufacture	Half Glazed Door	Double Low-E Soft	0.05		0.63		0.70	1.00
Windows	Manufacture	Window	Double Low-E Soft	0.05		0.63		0.70	1.20
Patio Door	Manufacture	Window	Double Low-E Soft	0.05		0.63		0.70	1.40
Rooflights	Manufacture	Roof Window	Double Low-E Soft	0.05		0.63		0.70	1.20

13.0 Openings

Name	Opening Type	Location	Orientation	Curtain Type	Overhang Ratio	Wide Overhang	Width (m)	Height (m)	Count	Area (m ²)	Curtain Closed
Front Entrance	Half Glazed Door	[1] External Wall	South East							2.10	
Front Windows	Window	[1] External Wall	South East	None	0.00					3.80	
Rear Windows	Window	[1] External Wall	North West	None	0.00					2.88	
Patio Doors	Window	[1] External Wall	North West	None	0.00					3.78	
LHS Windows	Window	[1] External Wall	South West	None	0.00					1.76	

14.0 Conservatory

15.0 Draught Proofing

 %

16.0 Draught Lobby

17.0 Thermal Bridging

17.1 List of Bridges

Source Type	Bridge Type	Length	Psi	Imported
Independently assessed	E2 Other lintels (including other steel lintels)	10.07	0.040	No
Independently assessed	E3 Sill	7.26	0.027	No
Independently assessed	E4 Jamb	15.60	0.029	No
Independently assessed	E5 Ground floor (normal)	24.60	0.049	No
Independently assessed	E6 Intermediate floor within a dwelling	24.60	0.003	No
Independently assessed	E10 Eaves (insulation at ceiling level)	9.25	0.083	No
Independently assessed	E12 Gable (insulation at ceiling level)	8.05	0.054	No
Independently assessed	E16 Corner (normal)	9.99	0.050	No
Table K1 - Default	E18 Party wall between dwellings	9.99	0.120	No
Table K1 - Default	P1 Party wall - Ground floor	8.05	0.160	No
Table K1 - Default	P2 Party wall - Intermediate floor within a dwelling	8.05	0.000	No
Table K1 - Default	P4 Party wall - Roof (insulation at ceiling level)	8.05	0.240	No

Y-value	<input type="text" value="0.053"/>	W/m ² K
---------	------------------------------------	--------------------

18.0 Pressure Testing

Designed AP ₅₀	<input type="text" value="5.00"/>	m ³ /(h.m ²) @ 50 Pa
Property Tested ?	<input type="text"/>	

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

As Built AP₅₀

m³/(h.m²) @ 50 Pa

19.0 Mechanical Ventilation

Summer Overheating

Windows open in hot weather	Windows fully open
Cross ventilation possible	Yes
Night Ventilation	No
Air change rate	8.00

Mechanical Ventilation

Mechanical Ventilation System Present	No
---------------------------------------	----

20.0 Fans, Open Fireplaces, Flues

	MHS	SHS	Other	Total
Number of Chimneys	0		0	0
Number of open flues	0		0	0
Number of intermittent fans				3
Number of passive vents				0
Number of flueless gas fires				0

21.0 Fixed Cooling System

No

22.0 Lighting

Internal

Total number of light fittings	1	
Total number of L.E.L. fittings	1	
Percentage of L.E.L. fittings	100.00	%

External

External lights fitted	No
------------------------	----

23.0 Electricity Tariff

Standard

24.0 Main Heating 1

Database	Database	
Percentage of Heat	100	%
Database Ref. No.	17959	
Fuel Type	Mains gas	
Main Heating	BGW	
SAP Code	104	
In Winter	90.2	
In Summer	76.2	
Controls	CBI Time and temperature zone control	
PCDF Controls	0	
Delayed Start Stat	Yes	
Sap Code	2110	
Flue Type	Balanced	
Fan Assisted Flue	Yes	
Is MHS Pumped	Pump in heated space	
Heat Emitter	Radiators	
Flow Temperature	Normal (> 45°C)	
Combi boiler type	Standard Combi	
Combi keep hot type	None	

25.0 Main Heating 2

None

SUMMARY FOR INPUT DATA

Calculation Type: New Build (As Designed)

Community Heating	None
28.0 Water Heating	HWP From main heating 1
Water Heating	Main Heating 1
Flue Gas Heat Recovery System	No
Waste Water Heat Recovery Instantaneous System 1	No
Waste Water Heat Recovery Instantaneous System 2	No
Waste Water Heat Recovery Storage System	No
Solar Panel	No
Water use <= 125 litres/person/day	Yes
SAP Code	901
29.0 Hot Water Cylinder	None

Recommendations

Lower cost measures

None

Further measures to achieve even higher standards

	Typical Cost	Typical savings per year	Ratings after improvement	
			SAP rating	Environmental Impact
Solar water heating	£4,000 - £6,000	£30	B 85	
	Typical Cost	Typical savings per year	Ratings after improvement	
			SAP rating	Environmental Impact
Solar photovoltaic panels, 2.5 kWp	£3,500 - £5,500	£345	A 96	